

Product Specifications for 2206A-E13TAG

Gross Mechanical Output	324-461 kWm
Typical Electrical Output	350-500 kVA (280-400 kWe)
Rated Speed	1500/1800 rpm
Prime	350-400 kVA
Standby	400-450 kVA
Prime	320-350 kWe
Standby	350-400 kWe
Emissions	Fuel Optimised
Number of Cylinders	6 vertical inline
Bore	130 mm
Stroke	157 mm
Displacement	12.5 l
Compression Ratio	16.3:1
Aspiration	Turbocharged and air-to-air charge cooled
Combustion System	Direct injection

Rotation from Flywheel End	Anti-clockwise
-----------------------------------	----------------

Cooling System	Liquid
-----------------------	--------

Aftertreatment	-
-----------------------	---

Typical Alternator Efficiency	92%
--------------------------------------	-----

Switchable	Yes
-------------------	-----

Length	2410 mm
---------------	---------

Width	1120 mm
--------------	---------

Height	1725 mm
---------------	---------

Dry Weight	1478 kg
-------------------	---------

Note 1	*Final dimensions dependent on selected options
---------------	---

Prime Power	Variable load, Unlimited hours usage with an average load factor of 70% of the published prime power rating over each 24 hour period, A 10% overload is available for 1 hour in every 12 hours of operation.
--------------------	--

Standby Power	Variable load, Limited to 500 hours annual usage up to 300 hours of which may be continuous running, No overload is permitted.
----------------------	--

2206A-E13TAG Standard Equipment

Air inlet system

Mounted air filter

Cooling system

Gear-driven circulating pump

Mounted belt-driven pusher fan

Radiator incorporating air-to-air charge cooler, (supplied loose)

System designed for ambients up to 50°C (122°F)

Electrical equipment

3 level engine protection system

24 volt starter motor and 24 volt 70 amp alternator with DC output

ECM mounted on engine with wiring looms and sensors

Flywheels and flywheel housing

High inertia flywheel to SAE J620 size 14

SAE 1 flywheel housing

Fuel system

Fuel cooler

Governing to ISO 8528-5 class G2 with isochronous capability

Mechanically actuated electronically controlled unit fuel injectors with full authority electronic control

Replaceable 'Ecoplus' fuel filter elements with primary filter/water separator

Mountings

Front engine mounting bracket

Oil system

Full-flow replaceable 'Ecoplus' filter

Oil cooler integral with filter header

Wet sump with filler and dipstick

Optional equipment

110 volt/240 volt immersion heater

Additional speed sensor

Air filter rain hood

Temperature and pressure sensors for gauges

Tool kit

Twin starters/facility for second starter

